

SPECIFICATIONS

UPC	00030317028787
Finish	Matte
Adjustable Objective	No
Reticle Focal Plane	First Focal Plane
Elevation Adjustment Type	M5C3
Locking Dial	Yes
Revolution Indicator	Yes
Rezero Type	Set Screw
Windage Adjustment Type	Capped
Custom Dial System (CDS)	No
BDC Dial Included	No
Reticle Type	Illuminated
Reticle	Illum. FFP PR1-MIL
Magnification Type	Variable
Battery Type	CR2032
Switch Type	Dial
Daylight Bright Illumination	No
Electronic Reticle Level	No
Guard-ion Lens Coating	No
Weight (oz)	26
Elevation Adjustment Value per Click	0.1Mil
Elevation Adjustment Range (MOA)	100
Elevation Adjustment Range (MIL)	29
Elevation Adjustment Range (cm @ 100m)	291
Elevation Adjustment Per Revolution	10.5 MIL
Elevation Dial Travel Limit	30MIL

Windage Adjustment Value per Click	0.1Mil
Windage Adjustment Range (MOA)	80
Windage Adjustment Range (MIL)	23
Windage Adjustment Range (cm @ 100m)	233
Windage Adjustment Per Revolution	10 MIL
Magnification Max	18
Magnification Min	3.6
Objective Lens Diameter (mm)	44
Linear FOV Low Mag (ft@100yds)	28.3
Linear FOV High Mag (ft@100yds)	5.8
Angular FOV Low Mag (Degrees)	5.4
Angular FOV High Mag (Degrees)	1.1
Eye Relief Low Mag (in)	3.5
Eye Relief High Mag (in)	3.8
Minimum Parallax-Free Distance (yd)	50
Battery Life (hr), Low Intensity	1800
Battery Life (hr), High Intensity	96
Number of Illum Settings	7