## **Specifications**

Mount Type Nikon Z Mount

Focal Length Range 100 - 400mm

Zoom Ratio 4x

Maximum Aperture f/ 4.5-5.6

Minimum Aperture f/ 32-40

**Format** FX

Maximum Angle of View (DX-format) 16° - 4°

Maximum Angle of View (FX-format) 24°20′ – 6°10′

Maximum Reproduction Ratio 0.38x

Lens Elements 25

Lens Groups 20

VR (Vibration Reduction) Image Stabilization Yes

Lens shift using voice coil motors (VCMs)

Diaphragm Blades 9

(rounded diaphragm opening)

ARNEO Coat Yes
Nano Crystal Coat Yes

ED Glass Elements 6

Super ED Glass Elements 2

Fluorine Coat Yes

**Autofocus** Yes

AF Actuator STM (stepping motor)

Internal Focusing Yes

Minimum Focus Distance 100mm zoom position: 2.46 ft (0.75m)

135mm zoom position: 2.56 ft (0.78m) 200mm zoom position: 2.63 ft (0.8m) 300mm zoom position: 2.86 ft (0.87m) 400mm zoom position: 3.22 ft (0.98m)

Focus Mode Auto/Manual Filter Size 77mm

(P = 0.75 mm)

Approx. Dimensions (Diameter x Length) 3.9 in. (98 mm) x 8.8 in. (222 mm) Distance to end of lens

from camera lens mount flange Based on CIPA guidelines

**Approx. Weight** 50.6 oz. (1435 g) Based on CIPA guidelines

50.6 ounces with tripod collar and 47.8 ounces without tripod

collar

1435 grams with tripod collar and 1355 grams without tripod
collar

Lens Type Zoom