

Tech Specs

Specifications

Measurement Range	8-1200 yd.Distance: 8-1,200 yd. (7.5-1,090m)
Increment Reading	Actual Distance: every 1m/yd. Actual Distance (lower): every 0.5m/yd. Slope Adjusted Distance (lower): every 0.2m/yd. Height (upper): every 1m/yd. (100m/yd. and over), Height (upper): every 0.2m/yd. (shorter than 100m/yd.)
Magnification	6-21x
Effective Objective Diameter	21mm
Angular Field of View (Real)	7.5°
Viewfinder Display	m/YD
Eye Relief	18mm
Diopter Adjustment	+/-±4 m-1°
Power Source	CR2 lithium battery
Size (Length x Width x Height)	4 in.4mmx1.7 in.1.7mmx2.9 in.2.9mm
Weight (Without Batteries)	7.2 oz7.2g
Operating Temperature	-10 to +50°C (14 to 122°F)
Operating Humidity	80% or less (without dew condensation)
Objective Diameter	21mm
Waterproof	Yes; (up to 1m/3.3ft for 10 minutes)
Battery Life	Approx.Approx. 2,700 measurements

Laser Classification	IEC60825-1: Class 1M/Laser Product FDA/21 CFR Part 1040.10: Class I Laser Product
Electromagnetic Compatibility	FCC Part15 SubPartB class B, EU:EMC directive, AS/NZS, VCCI classB, ICES-003, GB:Electromagnetic Compatibility Regulations
Environment	ROHS, WEEE
Wavelength (nm)	905
Pulse Duration (ns)	9.7
Output (W)	32.3
Beam Divergence (mrad)	Vertical: 0.25, Horizontal: 1.8
Use	Golf
Image Stabilization	Yes