

>> MS Series Studio Flash

// MS300 // MS200

MS Series Studio Flash offer high-quality lighting solutions to photographers of different levels. It is best for all portrait, fashion, wedding, and e-commerce product photography in small or medium studio shooting. In large studio shooting, it can function as high light, background light or hair light.

- Main Features:**
- Built-in 2.4G wireless X system
 - 50 steps of power output from 1/32 to 1/1
 - 150W modeling lamp adjusts from 5% to 100%
 - Anti-preflash function enables synchronization with cameras that have a one-preflash firing system
 - Auto memory and recovery of adjusted panel settings
 - Quickly installs various light modifiers such as softbox



- (1) AC Power Socket (2) Sync Cord Jack (3) Power Switch (4) Test Button
(5) Modeling Lamp Button (6) S1/S2 Slave Model Button
(7) Group/Channel Button (8) BUZZ Button (9) Wireless Control Port
(10) LCD Display (11) Light Sensor (12) Test Indicator (13) Select Dial + SET Button (14) Fuse (15) Mounting Bracket (16) Umbrella Input
(17) Direction Adjusting Handle



>> MS Flash Kit

// MS300 // MS200

The two-light kit of MS Series contains flash strobes, light stand, flash trigger and different light shaping accessories, which can be easily packed in a carrying bag.

- Model: **MS200-F, MS300-F**
2* MS Flash Head
2* Lighting Stand 304 (2m)
2* Softbox SB-BW (60X90cm)
1* Reflector
1* XT16 Transmitter
1* Carrying Bag CB-05



XT16



Specifications:		
Model	MS200	MS300
Max Power (Ws)	200Ws	300Ws
Guide Number(m ISO 100) (use with highly effective reflector)	53	58
Color Temperature	5600±200k	
Operating Voltage	AC110V-120V~60Hz//AC220-240V(50Hz)	
Power Output Control	5.0~10.0(1/32~1/1)	
Modeling Lamp (W)	150W	
Modeling Lamp Level	5%~100%	
Recycle Time	220V(0.1~1.3s)/110V(0.1~1.8s)	
Triggering Method	Sync cord, Test button, Slave triggering, Wireless control port	
Flash Duration	1/2000~1/800s	
Parameters output from the sync cord jack	5V	
Parameters output from the USB port	5V/200mA (only for Godox receiver)	
Fuse	F8AL 250V	
Dimension	Flash diameterΦ12.6cm, height of flash with handle 12.7cm length of flash with lamp cover 28.3cm	
Net Weight	Approx. 2.6kg	