
RIFLE TELESCOPES FOR PROFESSIONAL MARKSMEN

5-25x56mm model TT525P

Magnification	5x-25x
Length	425mm
Width	103mm
Height	86mm
Weight	1150g
Tube diameter	34mm
Objective bell diameter	65mm
Objective lens diameter	56mm nominal
Eyepiece diameter	45mm
Reticle options	Gen 2XR, MoA
Field of View @ 5x	4.3 degrees (7.6m @ 100m)
Field of View @ 25x	0.9 degrees (1.6m @ 100m)
Diopter range	-3 to +2.5
Eye relief	90mm
Exit pupil @ 5x	11mm
Exit pupil @ 25x	2.3mm
Re-zero mechanism	TOOL-LESS RE-ZERO® (patent pending)
Total Adjustment Range	
Elevation	30 mrad (103 MoA)
Windage	+/- 10 mrad (+/- 34 MoA)
Working Adjustment Range	
Elevation	28 mrad (96 MoA)
Windage	+/- 6 mrad (+/- 20 MoA)
Adjustment resolution	0.1 mrad or 1/4 MoA
Parallax adjustment range	50m to infinity
Crosshair illumination	LED, 11 settings
Battery type	DL2032 3v lithium
Exterior finish	Type II Anodized, matte
Environmental	
Waterproof:	4 hours @ 10 meters
Shockproof:	700g's @ 10,000 cycles
Standard accessories:	Tenebraex® lens covers & ARD