

Specifications

Model	X2T-C	X2T-N	X2T-S	X2T-F	X2T-O	X2T-P
Competible cameras	Canon EOS cameras (E-TTL II autoflash)	Nikon Cameras (i-TTL autoflash)	Sony Cameras (TTL autoflash)	Fujifilm Cameras (autoflash)	Olympus/ Panasonic Cameras (TTL autoflash)	Pentax Cameras (TTL autoflash)
	Work with cameras with PC sync socket					
Competible mobile phone	iPhone, HUAWEI, Samsung (Please refer to the compatibility list on the manual to know more about the compatible models.)					
Power supply	AA battery x2					
Flash exposure control						
TTL autoflash	E-TTL II	i-TTL	TTL	TTL	TTL	TTL
Manual Mode	✓					
Multiflash mode	✓					
Functions						
High-speed sync	✓					
Rear-curtain sync	✓					
Flash exposure compensation	✓, ±3 stops in 1/3 stop increments					
Flash exposure lock	✓					
Focus assist	✓					
Modeling lamp	✓					
Beeper	✓					
Wireless shutter release	The receiver can control the camera shooting via 3.5mm sync cord jack					
Zoom setting	Adjust the focal length of the flash through the transmitter					
Firmware upgrade	Support program firmware upgrade via Type C USB cable					
Memory function	As long as 2 seconds after setting parameters, the parameters will be remembered, and the original data will be recovered once restart.					
Wireless Flash						
Transmission range (approx.)	0-100m					
Built-in Wireless System	2.4G Wireless Transmission					
Modulation mode	MSK					
Channels	32					
Wireless ID	01-99					
Groups	5					
Others						
Display	A large LCD panel, backlighting ON or OFF					
Dimension (mm)	72x70x58					
Net weight (g)	90					