

TECHNICAL SPECIFICATIONS APM021DA10

CCT

5,600K

CRI

96+

TLCI

99+

CQS

95+

SSI (D56)

86+

TM-30 RF (Average)

96

TM-30 RG (Average)

103

Max Power Consumption

110.9W

Max Power Output

100W

Lumens

10,000lm

Beam Angle (No Reflector)

110.9°

Beam Angle (Hyper Reflector - Mini)

17.1°

Operating Voltage (DC Power Supply)

48V / 2.7A

Operating Voltage (AC Power Supply)

100V ~ 240V / 2.0A

Operating Temperature

-10°C ~ 40°C / 14°F ~ 104°F

Storage Temperature

-20°C ~ 80°C / -4°F ~ 176°F

Control Methods

On-board, Sidus Link App

Firmware Upgradeable

Sidus Link

Wireless Operating Range (Bluetooth)

≤100m / ≤328.1ft

Screen Type

LCD

Cooling Method

Active Cooling

DIMENSIONS

Lamp Head w/o Mounting Bracket

207 x 115 x 115cm / 81.5 x 45.3 x 45.3in

Lamp Head w Mounting Bracket

207 x 119 x 200cm. 81.5 x 46.9 x 78.7in

Power Supply

137.3 x 59.1 x 36.1mm / 5.41 x 2.33 x 1.42in

Power Cable

300cm / 118.11in

WEIGHT**Lamp Head**

1.42kg / 3.13lbs

Power Supply

490g / 1.08lbs

Total with Case

3.268kg / 7.20lbs