NIGHTFORCE

2.5-20x50 F1



- 8x zoom range, 2.5x to 20x magnification
- First Focal Plane (FFP/F1) reticle
- ED (Extra-low Dispersion) glass for superior image quality
- 50 mm objective lens for maximum resolution and low-light use
- Compact length at 12.0"/305mm
- 30 mm body tube
- Parallax adjustable from 11 yards to infinity

- ZeroStop elevation adjustment for rapid and easy return to zero
- 10 MRAD/20 MOA per turret revolution
- 32 MRAD/110 MOA of total elevation adjustment
- Capped windage adjustment
- Integrated PTL (Power Throw Lever)
- Locking diopter adjustment

Specifications

Focal Plane First Objective Outer diameter Tube diameter

59 mm 30 mm

Internal adjustment

e: 32 Mil; w: 23 Mil e: 110 MOA; w: 80 MOA

Click value Parallax adjustment

.10 Mil or .25 MOA 11 yds/10 m - ∞

Exit pupil

2.5x: 7.1 mm; 20x: 2.5 mm

Eye relief

87.5 mm/3.44 in

Field of view @ 100Y

2.5x: 41.8 ft; 20x: 7.0 ft

Eyepiece outer diameter

43 mm 12.0 in/305 mm

Overall length Weight

28.3 oz/802 g

Mounting length

5.44 in/138 mm

Reticle


Standard MOARTM, Mil-CTM

Illumination

Digillum™, Red & Green

The NX8 2.5-20x50 F1 riflescope is an ultra-compact and capable riflescope. Building upon the legendary durability of the NXS family from Nightforce, the NX8 adds first focal plane performance with an 8x zoom range in a small package. This wide zoom range allows for fast engagements at close range along with the ability to detect, identify and engage targets at long range.

Other features include the ZeroStop elevation adjustment for a rapid return to zero. The 50mm objective is optimized for resolution and light transmission, with a parallax adjustment coming as close as 11 yards. The integrated PTL (Power Throw Lever) makes power changes fast and easy. The performance available in such a compact size makes the NX8 2.5-20x50 F1 a perfect choice for your favorite semi-auto precision rifle or compact bolt-action rifle.



© Nightforce Optics, Inc. 2019 05/19 All information herein is accurate at time of printing Specifications and product appearances subject to change without notice