
RIFLE TELESCOPES FOR PROFESSIONAL MARKSMEN

3-15x50mm model TT315M

Magnification	3x-15x
Length	351mm
Width	84mm
Height	69mm
Weight	786g
Tube diameter	30mm
Objective bell diameter	57mm
Objective lens diameter	50mm nominal diameter
Eyepiece diameter	43mm
Reticle options	Gen 2, Gen 2XR, MoA
Field of View @ 3x	7.3 degrees (12.8m @ 100m)
Field of View @ 15x	1.6 degrees (2.8m @ 100m)
Diopter range	-3 to +2.5
Eye relief	90mm
Exit pupil @ 3x	11.5mm
Exit pupil @ 15x	3.5mm
Total Adjustment Range	
Elevation	18 mrad (60 MoA)
Windage	+/- 12 mrad (+/-40 MoA)
Working Adjustment Range	
Elevation	12 mrad (40 MoA)
Windage	+/- 6 mrad (+/- 20 MoA)
Adjustment resolution	0.1 mrad or 1/4 MoA
Re-zero mechanism	twin setscrew
Parallax adjustment range	50m to infinity
Crosshair illumination	LED, 11 settings
Battery type	DL2032 3v lithium
Exterior finish	Type II Anodized, matte
Elevation dial adjustment	
Double turn	6 mrad (20 MoA) per turn
Environmental	
Waterproof:	4 hours @ 10 meters
Shockproof:	700g's @ 10,000 cycles

Standard
accessories

Tenebraex® lens
covers & ARD
