

Tech Specs

Model	iT30Pro C	iT30Pro N	iT30Pro S	iT30Pro F	iT30Pro O
Guide Number (1/1 step)	Approx. GN15 (ISO 100, in meters)				
Flash Duration (t0.1)	1/1000s~1/30000s				
Global Shutter Sync Shooting	/	/	Provided	/	/
Radio Wireless Global Shutter Sync	/	/	Provided	/	/
Exposure Control					
Exposure Control System	E – TTL II Auto Flash Manual Flash	i – TTL Auto Flash Manual Flash	TTL Auto Flash Manual Flash	TTL Auto Flash Manual Flash	TTL Auto Flash Manual Flash
Flash Exposure	±3 steps with 1/3 increment each step				
Compensation (FEC)					
Sync Mode	High-speed sync (up to 1/8000 seconds, or 1/80000 seconds with Sony cameras equipped with global shutter), first-curtain sync, and second-curtain sync				
Multi Flash	Provided (up to 100 times, 100Hz)				
Wireless Flash (Radio 2.4G Transmission)					
Wireless Function	Sender, Receiver				
Sender Groups	A、 B、 C、 D	M、 A、 B、 C	M、 A、 B、 C	M、 A、 B、 C	M、 A、 B、 C
Receiver Groups	A, B, C, D				
Transmission Range (approx.)	100m				
Channels	32: 01~32				
ID	OFF/01~99				
Power Supply					

Lithium Battery	7.4V/ 900mAh
Recycle Time (1/1 step)	Approx. 1.5s
Number of Flashes (1/1 step)	Approx. 560
Power Saving	Provide standby and auto off functions
Sync Triggering Mode	Hot shoe, 2.5mm sync cord

Dimension

W x H x D	65mm×46mm×47mm
Net Weight	Approx.120g