Product Specifications

Camera Function

Image sensor	1/5 type CMOS primary color filter
Number of recorded pixels	2560 × 1920 pixels
Storage media	Internal memory,micro SD/micro SDHC memory card
Storage capacity	Approximately 45 images in internal memory, approximately 850 images per 1 GB in micro SD/micro SDHC memory card
Recording method	JPEG (DCF compliant Exif Ver. 2.3)
Focus distance	f = 28 mm (35 mm film equivalent)
Aperture	F2.0
Auto focus	Single AF (with AF Illuminator)
Shooting distance	10 cm to ∞
Shutter speed	1/4 second to 1/8000 second (automatic switching)
Shooting sensitivity	ISO100 to 1600 (automatic switching)
Exposure control	Program AE
Exposure	-2.0 EV to +2.0 EV (1/3 EV step)

Metering method	TTL 256 split metering, multi metering
White balance	Auto
Flash	Auto flash / Forced flash/Suppressed flash Shooting range with flash: Approximately 50 cm to 1.5 m
Self-timer	Approximately 2 seconds / approximately 10 seconds
Image effects	Filters, frames (3 available with shortcuts)
Sound recording	Possible to record sound when shooting or playing back single image. Possible to overwrite.

Print Function

Film used	FUJIFILM instant film instax™ mini (sold separately)
Number of films	10 films/pack
Film size	86 mm x 54 mm
Screen size	62 mm x 46 mm
Print pixel count	800 x 600 dots
Print resolution	12.5 dots / mm (318 dpi, 80 µm dot pitch)
Print gradation	RGB gradation of 256 colors
Printable image format	JPEG images taken with this unit

Print output time	Approximately 12 seconds
Print function	Images in the internal memory and images in the memory card can be printed
Reprint	Reprint is possible for images stored in Print history (up to 50)

Other

Smartphone App linked functions	Sound playback function from printed images, Smartphone image print function, remote shooting function, frame selection function
LCD monitor	2.7-inch TFT color LCD monitor Pixel count: Approximately 230,000 dot
External interface	USB Type-C port (for charging only)
Power supply	Lithium ion battery (internal type: not removable)
Charging function	Built-in battery
Possible number of	"Approximately 100 (from full charge)
printed images	The number of prints depends on the usage conditions."
Charging time	Approximately 2-3 hours
	Charging time depends on the temperature.
Main unit dimensions	82.5 mm × 122.9 mm × 36.7 mm (excluding projecting parts)
Main unit weight	Approximately 255 g

Operating environment	Temperature: +5 °C to +40 °C Humidity: 20% to 80% (no condensation)
Declaration of conformity	UK_Declaration of Conformity_FI043(LiPlay) EU_Declaration of Conformity_FI043(LiPlay)
License	<u>QR-Code-generator</u> LZ4

The above specifications are subject to change for performance improvement.