OLYMPUS°



TRACK YOUR ADVENTURES IN ULTRA HD



Available Colors:



Presenting an action cam that's tough enough to keep up with your adventures. The pocket-sized TG-Tracker records Ultra HD 4K video using advanced Olympus optics. Take it places you wouldn't dare take most cameras. Mountaintops. Winter slopes. Whitewater rafting or into the waves. Drop it, freeze it, submerge it, and it will just keep shooting – even 100 ft (30 m) underwater, no protective housing required. Handy extras like the LED headlight and the tilt-out monitor help you nail difficult shots. Use the built-in Action Sensors, GPS, and Wi-Fi to record and share every awesome moment. The TG-Tracker. It loves adventure as much as you do.

KEY FEATURES

- Ultra HD 4K Video
- 204° Extreme Angle F2.0 High-Speed Lens
- Electronic 5-Axis Image Stabilization
- 90° Tilt-Out LCD Monitor
- LED Headlight

- Built-In Wi-Fi
- Enhanced GPS & e.Compass
- Accelerometer
- Temperature Sensor
- Barometric Pressure Sensor











Tough TG-TRACKER



Image Sensor	1/2.3" BSI CMOS		
Lens	Construction: Open aperture F-value: Angle of view:	7 elements in 7 groups*1 f/2.0 Wide (diagonal angle of view 204 degrees) Underwater/Narrow*2 (diagonal angle of view 156 degrees) (IS off)	
Recording Media	Type: Capacity:	microSD/microSDHC/microSDXC Memory Card (commercially available) (UHS-I compatible) 128 MB - 128 GB	
Monitor	Type: No. of dots:	1.5-inch LCD monitor Approx. 115K dots	
Shutter speed	AUTO: 1/2 - 1/24000 sec.		
Movie Recording	Recording format: Recording mode: Continuous recording tin Image stabilization: Movie sound recording f	Electronic 5-axis image stabilization	
Still Image Recording	Compression method: Image size: Aspect ratio: Interval shooting: Self-timer:	JPEG 8M, 2.1M, 0.9M, 0.4M 16:9 0.5/1/2/5/10/30/60 sec. 2/12 sec.	
Tough Capability	Waterproof: Dustproof: Shockproof: Crushproof: Freezeproof:	30 m, IPX8 yes, IP6X 2.1 m 100 kgf -10°C	
Action Track Sensor System	GPS (GLONASS, QZSS), e.Compass, Atmospheric pressure sensor, Temperature sensor, Accelerometer		
LED Headlight	20 lumens (30 min.), 60 lumens (60 sec.)		
Wi-Fi	IEEE 802.1b/g/n	IEEE 802.1b/g/n	
Power supply	Lithium-lon battery: LI-	Lithium-lon battery: LI-92B	
Dimensions (CIPA guideline compliant)	35.0 (W) x 56.5 (H) x 93.2 (D) mm		
Weight (CIPA guideline compliant)	180 g (excluding battery	180 g (excluding battery and memory card)	
Box contents	LP-T01 Lens Protector, UP-T01 Underwater Protector, MC-T01 Mount Coupling, SG-T01 Steady Grip, Joint Screw, LI-92B Li-ion Rechargeable Battery, F-5AC AC Adapter for Camera Charging, CB-USB10 USB Cable, Strap		

^{*1} Not including the lens protector.

^{*2} When the UP-T01 underwater protector is mounted.














*Specifications and appearances are subject to change without any notice or obligation on the part of the manufacturer. *The colors of products printed herein may differ from those of the actual products. *HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered marks of HDMI Licensing LLC. *Wi-Fi is a registered trademark of the Wi-Fi Alliance. The Wi-Fi CERTIFIED Logo is a certification mark of the Wi-Fi Alliance. *All other company and product names are registered trademarks and/or trademarks of their respective owners. *The pictures in this catalog of the monitors and viewfinders are simulated. *The date herein is as of May 2016. © 2016 Olympus America

