

Product Specifications

Film used

FUJIFILM instax™ mini Instant Film (sold separately)

Photo Picture Size

62 mm × 46 mm

Lens

2 components, 2 elements, f = 60 mm, 1:12.7

Viewfinder

Real image finder, 0.37×, with target spot Features parallax correction function for Close-Up Mode

Shooting Range

0.3 m and beyond (use Close-Up Mode for 0.3 m to 0.5 m)

Shutter

Programmed electronic shutter 1/2 to 1/250 sec.

Slow synchro for low light

Exposure Control

Automatic, Lv 5.0 to 14.5 (ISO 800)

Film Ejection

Automatic

Film Developing Time

Approx. 90 seconds (varies depending on the ambient temperature)

Flash

Constant firing flash (automatic light adjustment), recycle time: 7 seconds or less (when using new batteries),
effective flash range: 0.3 m to 2.2 m

Power Supply

Two AA-size alkaline batteries (LR6), capacity: approx. 10 instax™ mini instant film packs of 10 exposures each per set of new batteries (depends on usage conditions)

* The supplied batteries are for initial use.

When they run out, replace them with new ones (Two AA-size alkaline batteries LR6 or Two AA-size nickel metal hydride batteries HR6).

* Do not mix alkaline and nickel metal hydride batteries.

* Manganese batteries cannot be used.

Auto Power Off Time

After 5 minutes

Self-timer

Electronic operating time: approximately 2 seconds / 10 seconds

Other

Includes film counter and film pack confirmation window

Dimensions

(W × H × D)

105.5 mm×124.7 mm×67.6 mm

Weight

327 g (without batteries, instax™ mini film loaded and strap attached)