Product Specifications

Camera function

Image sensor 1/5-inch CMOS with primary color filter

Number of recorded pixels 2560×1920

Storage media Internal memory, microSD/microSDHC memory card

Storage capacity Approximately 50 images in internal memory, approximately 850 images

per 1 GB in microSD/microSDHC memory card

Maximum number of shots

when the app is not

connected

50 shots

Recording method JPEG(DCF compliant Exif Ver 2.3)

Focus distance f = 16.25 mm (35 mm film equivalent)

Aperture F2.2

Shooting distance 19.4 cm to ∞

Shutter speed 1/4 second to 1/8000 second (automatic switching)

Shooting sensitivity ISO100 to 1600 (automatic switching)

Exposure control Program AE

Exposure compensation –2.0 EV to +2.0 EV (1/3 EV step)

Metering method TTL 256 split metering, multi metering

White balance Auto

Flash Automatic/OFF/ON

Shooting range with flash: Approximately 60 cm to 1.5 m

Self-timer Approximately 2 seconds / approximately 10 seconds

Zoom Not equipped

Other function

External interface USB Type-C port (for charging only)

Power supply Lithium ion battery (built-in type)

Charging time Approximately 2 to 3 hours

* Charging time depends on the

temperature.

Main unit dimensions 42.3 mm × 44.4 mm × 43.0 mm (excluding projecting parts)

Main unit weight Approximately 41 g

Operating environment Temperature: 5°C to 35°C

Humidity: 20% to 80% (no condensation)

Direct print compatible INSTAX mini Link™

models INSTAX mini Link2™

INSTAX SQUARE Link™
INSTAX Link WIDE™

Models that can print via the INSTAX mini Link™

app INSTAX mini Link2™

INSTAX SQUARE Link™

INSTAX Link WIDE™

INSTAX mini Evo™ INSTAX mini Liplay™

Shooting format INSTAX mini™

INSTAX SQUARE™
INSTAX WIDE™

Number of transfer data

mini: W600 \times H800 pixels SQUARE: W800 \times H800 pixels WIDE: W1260 \times

pixels

H840 pixels

Image transfer time mini: Approx. 10 sec/shot SQUARE: Approx. 15 sec/shot WIDE: Approx. 20

sec/shot

Declaration of conformity FCC_Declaration of conformity_FI026

<u>EU_Declaration of conformity_FI026</u> <u>UK_Declaration of conformity_FI026</u>

License LZ4

The above specifications are subject to change for performance improvement.