

**TENBA SKYLINE 13 Messenger Bag 637-613**

Exterior Dimensions: 14 in. W x 11.5 in. H x 6 in. D ( 36 X 29 X 15 cm )

Interior Dimensions: 13 in. W x 11 in. H x 5 in. D ( 33 X 28 X 13 cm )

Weight: 1.55 lbs ( 0.7 kg )

**Benro PP1 PocketPod Tabletop Tripod**

Camera Mounting Screw: 1/4"-20 Male

Load Capacity: 3.3lb (1.5kg)

Maximum Height: 5.3" (13.5cm)

Head Height: 6.9" (17.4 cm)

Folded Length: 6.9" (17.4 cm)

Weight: 5.6 oz (160g)

**Saramonic SR-BSP1C Mobile Device Mount with Cold Shoe Mount**

Construction: Aluminum

Supported Phone Sizes: 2.1 to 3.6" (5.3 to 9.1cm)

Dimensions: 3.54 x 1.7 x 1.1" (9 x 4.3 x 2.8cm)

Weight: 3.8oz (107g)

**Saramonic Vmic Mini Microphone**

Type: 14mm Condenser Microphone

Polar Pattern: Cardioid (Uni-Directional)

Frequency Range: 75Hz to 20kHz

Sensitivity: -35 ±3dB (0dB = 1V/Pa, @ 1kHz)

Maximum Input SPL: f=1kHz, THD<5% (105dB)

Output Impedance: 200ohm

Signal-to-Noise Ratio: 75dB SPL

Dimensions: 4.61 x 0.75 x 2.44" (117 x 19 x 62mm)

Weight: 2.43oz (69g)

Powered by Device (Plugin Power Required)

**MPOW MPPA071AB Wired Stereo Headset Microphone**

Compatibility: Windows 2000/7/8/10/XP/Vista, Mac OS X, Apple iOS (iPhone & iPad), Android Smartphones & Tablets

Output Connection Type: 3.5mm TRRS and USB-A

USB In-Line control with Mute and Volume Functions

Cable length: 7.9ft (2.4m)

Product Dimensions: 7.87" x 6.81" x 2.17"

Color: Black

Built in Noise Reduction Sound Card

Signal-to-Noise Ratio: ≥ 50db

Microphone Impedance: 2.2KΩ

Microphone Sensitiveness: -46 3dB

Loudspeaker diameter: 40mm

Loudspeaker sensitiveness: 103dB 3dB

Rated power: 10mW

Maximum power: 20mw

Loudspeaker Impedance: 16Ω

Frequency response: 20Hz to 20KHz

Powered by Device