

# Product Specifications

## Amaran 300C

<b>CCT</b>	2,500K –7,500K
<b>CRI</b>	95+
<b>TLCI</b>	95+
<b>CQS</b>	97+
<b>SSI (Tungsten)</b>	83+
<b>SSI (D56)</b>	71+
<b>TM-30 RF (Average)</b>	92
<b>TM-30 RG (Average)</b>	101
<b>Max Power Consumption</b>	360 W
<b>Max Power Output</b>	300 W
<b>Lumens</b>	19,389 lm (5,600K)
Beam Angle	
<b>No Reflector</b>	89.6°
<b>Hyper Reflector</b>	64.8°
Operating Voltage	
<b>Fixture</b>	DC 48V / 7.5A
<b>AC Power Supply</b>	100V ~ 240V / 2.5A / 50-60 Hz
<b>Operating Temperature</b>	-10°C ~ 40°C / 14°F ~ 104°F
<b>Storage Temperature</b>	-20°C ~ 80°C / -4°F ~ 176°F
<b>Control Methods</b>	On-board, SidusLinkApp
<b>Firmware Upgradeable</b>	SidusLink
<b>Wireless Operation Range</b>	≤100m / ≤328.1ft
<b>Screen Type</b>	LCD
<b>Cooling Method</b>	Active Cooling
Dimensions	
<b>Lamp Head w/o Mounting Bracket</b>	25.0 x 15.5 x 14.2cm (9.8 x 6.1 x 5.6")
<b>Lamp Head w/ Mounting Bracket</b>	25.0 x 19.4 x 25.1cm (9.8 x 7.6 x 9.9")
<b>Power Supply</b>	19.8 x 9.9 x 2.8 cm (7.8 x 3.9 x 1.1")
<b>DC Power Cable</b>	3m / 9.84ft
Weight	
<b>Lamp Head</b>	2.66 kg (5.86 lbs)
<b>Power Supply</b>	889 g (1.94 lbs)
<b>Total with Case</b>	3.32 kg (7.6 lbs)