

Specifications

Stabilizer

Tilt Mechanical Range

320°

Roll Mechanical Range

320°

Pan Mechanical Range

360°

Battery

Operation Voltage

Max: 12.6v / Min: 9.6v

Operation Current

Max: 4000mA / Min: 135mA

Output

5V, 1A

Battery Runtime

Max: 1H35min (lab data)

Charging Time

1H41min (lab data)

Size & Weight

Product Size (W*D*H)

240*68*150mm

Net Weight

~550g/unit

What's in the Box

Crane M2S Stabilizer x1

Mini Tripod x1

USB Cables x3

Fill Light Filters x4

Phone Clamp x1

EPP Storage Case x1

Backpack x1

Camera Compatibility List

Sony

FX3, A7R4, A7R3, A7R2, A7M3, A7M2, A7S2, A7S3, A7C, A6600, A6500, A6400, A6300, A6100, ZV-1, ZV-E10' RX100M7, RX100M6, RX100M5A, RX100M5, HX90

Nikon

Z5, Z6, Z6II, Z7, Z7II, Z30, Z50, ZFC

Canon

M50, M50 MARK II, M6 MARK II, R, R10, RP, 200D II, G7 X MARK III,

Panasonic

GH5, GH5S, DC-G100, ZS110, LX10, LX100M2

FUJIFILM

X-T3, X-T4, X-A7

SIGMA

FP