

## Sightmark Latitude 6.5-25x56 PRS Riflescope SM13042PRS



## Description

Designed for long-range competition shooting and Precision Rifle Series matches, the Sightmark Latitude 6.25-25x56 PRS Riflescope takes skilled shooters the full distance with extreme accuracy. We listened to everything competition shooters wanted out of an optic and built the Latitude with oversized turrets for quick and easy adjustments, a zero stop elevation dial and an etched, first focal plane reticle with red/green illumination for true dimensions at any magnification. The Latitude's locking, fast focus eyepiece keeps the focus set so shooters can focus their attention on Making Their Mark. The rugged Latitude 6.25-25x56 is IP67 waterproof, able to withstand up to .50 BMG recoil and built with a single-piece 34mm tube with a distance-friendly adjustment range of 31mil. The fully multi-coated Latitude includes a sunshade, CR2032 battery and instruction manual.

▲ WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## Features

• Oversized adjustment turrets

- Zero stop elevation dial
- · Locking, fast focus eyepiece
- 34mm single-piece tube
- · Red/green illuminated reticle
- 4:1 zoom ratio
- Scratch-resistant lens

First focal plane PRS reticle

- Aircraft grade aluminum
- Waterproof, fogproof and shockproof

## Specifications

Reticle	PRS
Reticle, Type	Etched glass
Illuminated (yes/no)	Yes, red/green
Reticle Brightness Setting	0-5
Magnification	6.25-25
Diameter, Objective Lens	56 mm
Objective overall dimension (mm)	2.4 / 61 in/mm
Diameter, Eyepiece	1.81/46 in/mm
Diameter, Exit Pupil	9.6-2.4 mm
Eye relief (in/mm)	4.7-4.2/120-107 in/mm
Field of view, m@100m	6.6-1.46
Field of view, ft@100yd	16.1-4
Diopter Adjustment	+2 to -2
Diameter, Tube	34 mm
Adjustment Value	.1 MRAD
Parallax Setting	20 - infinite Yards
Elevation adjustment range (MIL)	31 MIL
Travel Per Rotation	10 MRAD
Windage adjustment range (MIL)	20 MIL
Maximum Recoil	50 BMG Caliber

Battery Type	CR2032
Battery Life	30-2,000 Hours
Battery Voltage	3 V
Sunshade	Yes
Fog Proof	Yes
Shockproof	Yes, 3ft / .9m
Nitrogen Filled	Yes
Focal Plane	First
IP Rating (waterproof)	IP67 - waterproof to 1m/3ft for 1 hour
Finish/Color	Matte black
Body Material	Aluminum
Lens Coating	Fully multi-coated
Operating temperature, F/C	-20 to 160 / -29 to 71 F/C
Length (in/mm)	13.77 / 350 in/mm
Width (in/mm)	3.54 / 90 in/mm
Height (in/mm)	2.95 / 75 in/mm
Weight, oz	33.1 oz.

© 2020 Sightmark

http://www.sightmark.com

Created 07.07.2020