

Tech Specs

Specifications

Accuracy (Actual Distance)	±1 m/yd. (shorter than 100m/yd.)
Magnification	6x
Exit Pupil	3.3mm
Eye Relief	16.7mm
Diopter Adjustment	+/-4°
Power Source	1 CR2 Lithium Battery (DC 3V), Automatic power shut-off (after approx. 8 sec. unoperated)
Size (Length x Width x Height)	91 in.91mmx37 in.37mmx73 in.73mm
Weight (Without Batteries)	4.6 oz4.6g
Operating Temperature	-10 to +50°C (14 to 122°F)
Operating Humidity	80% or less (without dew condensation)
Battery Life	Approx.10,000 times (at approx. 20°C (68°F)) , *This figure may differ according to conditions such as temperature and other factors. Use only as a guide.
Laser Classification	IEC60825-1: Class 1M/Laser Product, FDA/21 CFR Part 1040.10: Class I Laser Product
Electromagnetic Compatibility	FCC Part15 SubPartB class B, EU:EMC directive, AS/NZS, VCCI classB, CU TR 020, ICES-003, GB:Electromagnetic Compatibility Regulations
Wavelength (nm)	905
Pulse Duration (ns)	20
Output (W)	15.2

Beam Divergence (mrad)

Vertical: 2.5 , Horizontal: 0.2

Use

Golf