

SQUARE SQ1

Specifications

| Model Name | FUJIFILM Instax® SQUARE SQ1 |
|----------------------|--|
| Film | Fujifilm Instant Film "INSTAX Square" (Sold Separately) |
| Image Size | 62 mm x 62 mm (2.4 inch x 2.4 inch) |
| Lens | 2 components, 2 elements, f = 65.75 mm 1:12.6 |
| Viewfinder | Reverse Galilean finder, 0.4×, with target spot |
| Shooting Range | 0.3 m (11.8 inch) and beyond (use selfie mode for 0.3 m (11.8 inch) to 0.5 m (19.7 inch)) |
| Shutter | Programmed electronic shutter 1/2 to 1/400 sec. Slow synchro for low light |
| Exposure Control | Automatic, Lv 5.0 to 15.5 (ISO 800) |
| Film Ejection | Automatic |
| Film Developing Time | Approx. 90 seconds (varies depending on the ambient temperature) |
| Flash | Constant firing flash (automatic light adjustment), recycle time: 7.5 seconds or less (when using new batteries), effective flash range: 0.3 m (11.8 inch) to 2.2 m (7.2 feet) |
| Power Supply | Two lithium batteries(CR2, included), capacity: approx. 30 INSTAX SQUARE film packs under FUJIFILM test conditions |
| Auto Power Off | After 5 minutes |
| Others | Includes film counter and film pack confirmation window |
| Dimensions | 130.7 mm × 118.6 mm × 57.5 mm (5.15 inch × 4.67 inch × 2.26 inch) |
| Weight | 390 g (without batteries, strap, and film) |