

Product Specifications

Recording method	3-color exposure with OLED
Film used	FUJIFILM INSTAX Mini Instant Film (sold separately)
Image size	2.4 in × 1.8 in / 62 mm × 46 mm
Exposure pixel count	800 × 600 dots
Exposure resolution	12.5 dots/mm (318 dpi, 80 µm dot pitch)
Exposure gradation	RGB gradation of 256 colors
Interface	Bluetooth Ver. 4.2 (BLE)
Printable image format	JPEG, PNG, HEIF, DNG
Printing time	Image recording - photo output (fed out): Approximately 15 sec.
Possible number of printed images	Approximately 100 (from full charge; number of prints depends on usage conditions)
Power supply	Lithium ion battery (internal type: not removable)
Charging time	Approximately 80 to 120 minutes (depending upon environment temperature at time of charging)
Power consumption	Approximately 3 W

Operating environment	Temperature: +41 °F to +104 °F (+5 °C to +40 °C) Humidity: 20% to 80% (no condensation)
Main unit dimensions	3.6 in × 1.4 in × 4.9 in / 91.9 mm × 36.4 mm × 124.8 mm (excluding projecting parts)
Main unit mass	Approximately 0.46 lbs / 210 g (excluding film pack)
Supplied accessory	Micro USB cable (BOD700-200, Length: 11.8 in / 30 cm)

Images of instax printing are for illustrative purposes only.

After an image is shot, it takes a short amount of time to display on the screen.

The above specifications are subject to change for performance improvement.

Image size may affect print finish (sharpness, grain, etc.).

Time required for wireless communication may be affected by file size, smartphone model, etc.

Print finish (color, image quality, etc.) may be affected by smartphone model, shooting conditions, etc.

Actual print finish may differ from the image displayed on the LCD screen of your smartphone.

Smartphone screen images are superimposed.

The Bluetooth® word mark and logo are registered trademarks of Bluetooth SIG, Inc. and FUJIFILM Corporation uses these under license.

QR code is a registered trademark of DENSO WAVE INCORPORATED.